

SPECIFICATION



Part No.: NSP-S0303

Features

- No UV or IR light radiation.
- Easy Installation
- Long lifetime: 50000 hours
- Correlated Color Temperature: 3000-6000K
- DC24V.
- External Driver
- LED type: 3014SMD Epistar
- 3 Years Warranty
- CE, RoHS Certified



NEWSTAR LED Lighting



调色温 (射频) LED面板灯连线图
CCT Dimmable LED Panel Light Wiring

Technical Specifications


Power	24W	CRI	>80
Lumens	1800LM	Frequency Range	50-60Hz
Fixture efficiency	>0.92	Color Temperature	3000-6000 Adjustable
Power Factor	>0.95	Fixing Ways	Recessed, Suspending
Light Source	224pcs SMD3014 Epistar	Dimension	295*295*9mm
Storage Temperature	-25°C ~ +65°C	Working Temperature	-30°C ~ +50°C
Body& Lampshade	Aluminum Alloy and PC	IP Grade	IP44

SPECIFICATION


Installation Instructions

Replace the plaster false ceiling


This is the most popular installation for the panel, remove the False ceiling and replace it with the panel




Suspended to the ceiling



i . Fix the 4 sockets to the ceiling with screws




ii . Screw the 4 ropes to the sockets




iii. Screw to the Led panel light. The height is adjustable by pulling the rope on the socket

Mounted on the ceiling or the wall



i . Fix the frame to the ceiling or wall with screws



ii . Screw the 4 clips to the panel



iii. push the panel to the frame and it will be clipped and fixed

SPECIFICATION

Application

- Home and office lighting.
- Hotel lighting.
- Super market lighting
- Warehouse lighting
- Airport lighting
- Factory lighting
- Classroom lighting
- Other light sources



LED PANEL LIGHT

Dimmable

Bright to dark
as you want

Bright Light
100%

Dim Light
20%

CCT Change

for different needs
Find your own style

Warm White
100%

Cool White
100%